

SALES & ENGINEERING DATA


650383 - X43 TWO-BALL PUMP SERIES

RATIO
SERIES: **6:1**

FLUID PSI
RANGE: **180 - 900**

RELEASED: 12-12-95
REVISED: 5-27-10
(REV. 02) S-830

DIMENSIONAL DATA



SPECIFICATIONS

CONSTRUCTION

Model Series (Refer to option chart below) 650383-X43
Type Air Operated, Two Ball
Ratio 6:1
Air Motor 65365
Motor Repair Kit 637041
Motor Diameter 3-1/4" (8.3 cm)
Stroke 6"
Air Inlet 1/4" - 18 NPTF-1(f)
Air Exhaust 1-1/4", 11-1/2 NPTF-1(f)
Lower Pump End Series 66300-X43
Lower Pump Repair Kit 637305-X43
Packing Options:

3 - PTFE	P - UHMW-PE/PTFE St'gd • UHMW-PE Lower
C - UHMW-PE	R - PTFE/UHMW-PE St'gd • PTFE Lower
G - UHMW-PE /Leather	

Material Inlet 1" 11-1/2 NPTF-1(f) &
2" 11-1/2 PTF (m) (SHORT)
Material Outlet 1" 11-1/2 NPTF-1(f)
Lower Pump End Materials:①
Outlet Body CF8M Stainless Steel
Cylinder 316 S.Stl Hard Chrome
Plunger 17- 4 S.Stl Hard Chrome
Upper Ball 316 Stainless Steel
Upper Seat Tungsten Carbide
Lower Ball 316 Stainless Steel
Lower Seat Tungsten Carbide
Inlet Body CF8M Stainless Steel
Weight 35.5 Lbs (16.1 Kgs)

PERFORMANCE

Air Inlet Pressure Range 30 - 150 PSI (2 - 10.3 bar)
Fluid Pressure Range 180 - 900 PSI (12 - 62 bar)
Max. Rec'd Cycles / Minute ... 60
Displacement In³ Per Cycle ... 14.5
Volume/Cycle 8 oz. (238 ml)
Cycles Per Gallon② 15.9
Flow @ 60 Cycles / Minute ... 3.7 GPM (14.3 lpm)
Noise Level @ 60 Psi - 40 Cpm③ 74.8 db(A)

Notes:

- ① All wetted components are passivated or electro-polished and have corrosion resistance characteristics of 300 Series Stainless Steel.
- ② 231 Cubic Inches = 1 Gallon
- ③ Tested with 91790 Silencer installed.

INGERSOLL RAND COMPANY LTD

209 NORTH MAIN STREET - BRYAN, OHIO 43506

① (800) 495-0276 • FAX(800) 892-6276

© 2010

CCN 15268709

www.ingersollrandproducts.com

ARO 
Industrial Technologies

PERFORMANCE CURVES

TWO BALL PUMP, 3-1/4" AIR MOTOR, 6" STROKE, 6:1 RATIO

