


**Pressure Range:** 30 to 150 PSIG (2.1 to 10.4 bar)  
**Temperature Range:** 32 to 160 F (0 to 71 C)  
**Flow & Cv Factor:** 1/8" Ports: 7.5 SCFM & Cv = .195  
 5/32" (4 mm) Tube Fittings: 4.0 SCFM & Cv = .104  
**Port Types:** Model 460-( ), 1/8" NPT Ports  
 Model 461-( ), 5/32" Tubing Ports  
**Actuating Force:** 3 lbs.  
**Stroke Length:** 5/64 (2.0 mm)


**REVISED:** 2-5-01  
**PN** 119999-43



**Air Supply:** For optimum service use an Aro Filter-Regulator-Lubricator combination unit between the valve and the air supply.

**Mounting:** The body has two mounting holes (use No. 10 screws) for surface mounting. For panel mounting applications, drill panel (3/16 (4.8) max. thickness) as shown in drilling layout. Mount the valve (and guard, if used) to the panel with the four Y195-34-C screws. Attach palm button.

The two 3/8 (9.5) dia. holes are required for button removal only for models with guard. To remove the button, insert probes thru the 3/8 (9.5) dia. holes & push the button off the plunger.



Dimensions given in Inches and (Millimeters).

